







Safe, sustainable, affordable, and accessible aviation for transformational local and intraregional missions



# Advanced Air Mobility (AAM): Bringing Aviation into Daily Life

- Three primary mission categories:
  - Urban Air Mobility (UAM)
    - "Local" missions up to ~75 miles around metropolitan areas
    - Largely novel "vertiport" infrastructure
    - eVTOL, potentially eSTOL or eCTOL aircraft
    - 1 to ~6 passengers or equivalent cargo
  - Small Unmanned Aircraft Systems (sUAS)
    - Local missions for aerial work or small cargo delivery (e.g., food, small packages)
    - Range of required takeoff/landing infrastructure from none to specialized
    - Typically VTOL-capable aircraft
  - Regional Air Mobility (RAM)
    - "Intraregional" missions up to ~500 miles
    - Primarily utilize existing (smaller) airports
    - eCTOL and eSTOL aircraft
    - Up to 19 passengers or equivalent cargo



- AAM is generally enabled by electrification & automation
- Many potential uses, including
  - Passenger transport
  - Cargo/package delivery
  - Emergency services/public good (e.g., air ambulance, EMT transport, etc.)
  - Aerial work (e.g., infrastructure inspection, photography, tourism, etc.)



# **Addressing AAM Challenges**









**Airspace Design** and Operations





**Community Integration** 



NASA and key partners are collectively taking on the most difficult mission challenges to enable industry to flourish by 2030

- Research and Development Portfolio
- AAM National Campaign Series
- Robust Ecosystem Partnerships



# **AAM Ecosystem Working Groups**

Align on a common vision for AAM

Learn about NASA's research and planned transition paths

Adopt a strategy for engaging the public on AAM



Collectively identify and investigate key hurdles and associated needs

Develop AAM system and architecture requirements

Support regulatory and standards development

Form a connected stakeholder community

See <a href="https://nari.arc.nasa.gov/aam-portal/">https://nari.arc.nasa.gov/aam-portal/</a> for more information

Accelerate the development of safe and scalable AAM flight operations by bringing together the broad and diverse ecosystem





# **AAM** is Convergence of the General Aviation and UAS Communities



AAM can be traced back to the early 2000s. Interest has grown exponentially since the late 2010s.





# **BACK-UP**

# NASA

#### What is an eVTOL aircraft?

- eVTOL = electric vertical takeoff and landing
  - Mix of all-electric, hybrid-electric, fuel cell power systems
- Many configurations no clear "dominant configuration"
  - Multirotor, (multi) tiltwing, (multi) tiltrotor, fan-in-wing, separate lift
    + cruise, compound helicopter, tiltduct, blown flap/tiltduct, advanced rotorcraft, etc.
- Common characteristics:
  - 1 to 6 person payload
  - Shorter hover duration than typical rotorcraft
  - Often considerably shorter ranges than conventional aircraft









# **Airport Considerations: Electrification**

#### Installation of chargers

- Accessible locations for all operations
- Consider use also for ground vehicles
- Ongoing charging standardization discussions
- How to monetize charging?
- Connectivity to electrical grid
  - Potentially large additional power requirements (multi-MW)
  - Long lead times
- Microgrids/renewables
  - Potentially large available land area
  - Sustainable energy supply for aviation and/or to improve local electricity grid



Roanoke Airport diagram from FAA's Chart Supplement





Solar arrays outside of runway object free area at Chattanooga Airport (CHA)

Imagery from NationalMap.gov



# **Other Airport Considerations**

- Improved multi-modal connectivity for FBOs
  - AAM operations not likely to use existing Part 121 passenger terminals
  - Mode change times need to be kept small
  - RAM and some UAM ops likely to utilize existing airport runways
  - FBOs may partner with indirect/direct air carriers
- Consider inclusion of new vertipads at airports
  - Ideally direct passenger access to existing passenger terminals (at larger airports)
  - Enable deconflicted approach/departure paths with existing air traffic

on a parking garage at RIC

Notional vertipad locations

Imagery from Google Maps ©2021 Commonwealth of Virginia, Maxar Technologies, USDA Farm Service Agency

Airport diagram showing existing helipad at EZF (Shannon Airport, Fredericksburg) from the FAA's Chart Supplement

Residentia

Helipad H1: 30 X 30



# **Vertiports**

- Many potential locations
  - Greenfield sites
  - Rooftops
  - Parking garages
  - Barges
  - New overpasses / cloverleafs?
  - Etc.
- Many siting considerations
  - Multi-modal connectivity
  - Noise
  - Utilities (electric grid)
  - Proximity of other vertiports/pads
  - Equity
  - Etc.
- Vertiport design guidelines under development



